

Datasheet Laro paper

General definition

Packaging tape made of kraft paper and provided with a glue layer based on natural rubber.

Features

- Good printing possibilities*
- Tape can be torn by hand
- Moisture resistant
- Adhesive strength increases as the tape is stuck longer
- Fits for both light and heavier packaging acts
- Suitable for recycling

*Attention: Brown paper tape has less printing possibilities. Following PMS colours can be chosen: Yellow 109, Reflex Blue, Black, Warm red, Green, White, Process blue

Specifications

Product type	Glue layer	Tape thickness in $M\mu$	Adhesive power on steel	Available Colors
Laro paper	Natural rubber	110±10% tolerance	2,5 N/cm±0,6	$\bigcirc \bigcirc$

Grammage of glue: 60 gr per m² • Foil type: paper provided with a coating

Storage advice

Temperature

This product can best be stored at a room temperature in a non humid room. We recommend a constant temperature between 15 and 23 degrees Celsius. If the temperature is lower, it can happen that the tape tears. This can also occur as a result of a damaged tape dispenser. Also using good tools is important (high quality dispenser). Printed tape is best processed at room temperature.

Sunlight/UV

This product can best be stored in a dark room. If too much sunlight (UV radiation) is exposed to the tape, the colour fastness can be affected. There may be deviations in the colour fastness.

Damages

Make sure that the tape rolls do not fall. This prevents damage in the tape that could cause the tape will tear.

Shelf life

How long can I keep this product? This depends on the degree to which the above-mentioned storage advice has been complied with. The guideline for a Paper tape is 6 months. No rights can be derived from this guideline.

Visiting address Vermeerstraat 15 7731 SM Ommen The Netherlands Postal address Postbus 59 7730 AB Ommen The Netherlands E info@larotape.nl
W www.larotape.nl
T + 31(0)529 - 45 38 55
F + 31(0)529 - 45 62 89